

Description


IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 1.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Factory sealed termination chamber
Energy efficiency	- Gimbal mounted, 355° rotatable and 20° tilt - option with Anti-Slip ceramic Coating ASC available on request

Additional information

Lifetime	LED >60,000 h Ta 25°(B10/70) Control gear >50,000 h Ta 25°
----------	---

Options**Light distribution Colour temperature Nominal Watt**

[M]



3000K

6 W

9 W



[EE]



4000K






[EES]



2700K

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [EE]	185-9796	LED-3/6W/2700K	605.8 lm	6 W	80
	185-7593	LED-3/6W/3000K	650.7 lm	6 W	80
	185-7593	LED-3/6W/3000K	650.7 lm	6 W	80
	185-7593	LED-3/6W/3000K	650.7 lm	6 W	80
	185-7596	LED-3/6W/4000K	695.6 lm	6 W	80
	185-7596	LED-3/6W/4000K	695.6 lm	6 W	80
	185-7596	LED-3/6W/4000K	695.6 lm	6 W	80
	185-7785	LED-3/9W/2700K	1009.5 lm	9 W	80
	185-7737	LED-3/9W/3000K	1058.8 lm	9 W	80
	185-7741	LED-3/9W/4000K	1108 lm	9 W	80
 [EES]	185-9797	LED-3/6W/2700K	652.3 lm	6 W	80
	185-7682	LED-3/6W/3000K	700.7 lm	6 W	80
	185-7682	LED-3/6W/3000K	700.7 lm	6 W	80
	185-7684	LED-3/6W/4000K	749 lm	6 W	80
	185-7684	LED-3/6W/4000K	749 lm	6 W	80
 [M]	185-9795	LED-3/6W/2700K	648.3 lm	6 W	80
	185-7592	LED-3/6W/3000K	696.3 lm	6 W	80
	185-7595	LED-3/6W/4000K	744.3 lm	6 W	80
	185-7784	LED-3/9W/2700K	920.5 lm	9 W	80
	185-7736	LED-3/9W/3000K	965.4 lm	9 W	80
	185-7740	LED-3/9W/4000K	1010.3 lm	9 W	80