

Description

RGBW/RGBA Colour Changer. IP67*, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. Cable gland with spiral cable bending protection. Integral EC electronic converter in thermally separated compartment. 'No tool' removable gear/lens tray. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with WE-EF Colour Boost Technology. DMX interface. Gimbal mounted, 360° rotatable and 30° tiltable.

The optional installation blackout is recommended for mounting. To be ordered separately.

Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request.

The luminaire is not suitable for permanent underwater operation and must be switched off in the event of flooding.

* Additionally tested to IP66, IP67, IP68 0.1 bar 3h, up to

1 m depth according to DIN EN 60598 and IP69K/80°
according to DIN EN 60529.

Specifications

Material description

Colours



Stainless Steel

Ingress protection IP67

Impact resistance IK10+

Electrical description

Surge protection 1/2 kV (optional SP10)


Energy efficiency C-D (Light source)

Additional information

Lifetime Ta=25° L90B10 > 90000h


Options

Light distribution


 [B] symmetric, wide beam


4000K+RGBW

19 W





 [M] symmetric, medium beam

RGBA

 [A6] asymmetric, wallgrazer

 [A20] wallwash

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A20] wallwash	185-3392	LED-12/19W/4000K+RGBW	1366 lm	19 W	80
	185-3417	LED-12/19W/RGBA	1302.2 lm	19 W	80
 [A6] asymmetric, wallgrazer	185-3391	LED-12/19W/4000K+RGBW	1445.5 lm	19 W	80
	185-3416	LED-12/19W/RGBA	1377.9 lm	19 W	80
 [B] symmetric, wide beam	185-3389	LED-12/19W/4000K+RGBW	1483.8 lm	19 W	80
	185-3414	LED-12/19W/RGBA	1414.5 lm	19 W	80
 [M] symmetric, medium beam	185-3390	LED-12/19W/4000K+RGBW	1479.5 lm	19 W	80
	185-3415	LED-12/19W/RGBA	1410.4 lm	19 W	80