

### Description

IP69, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 1.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

---

### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter

---







### Additional information

---





Lifetime	LED >60,000 h Ta 25°(B10/70) Control gear >50,000 h Ta 25°
----------	---

---

**Options****Light distribution    Colour temperature    Nominal Watt**

	[EE]		3000K	12 W
	[M]		4000K	
	[B]			
	[EES]			

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7224	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-7222	LED-6/12W/4000K	1457.5 lm	12 W	80
[B]					
	185-7217	LED-6/12W/3000K	1497 lm	12 W	80
	185-7220	LED-6/12W/4000K	1600.3 lm	12 W	80
[EE]					
	185-7225	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7223	LED-6/12W/4000K	1736.8 lm	12 W	80
[EES]					
	185-7218	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7221	LED-6/12W/4000K	1637.4 lm	12 W	80
[M]					