

Description

Tunable White. ASC Lens accessory can be added.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Cable gland with spiral cable bending protection. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver, thermally separated. OLC® One LED Concept. Factory-installed LED circuit board. Tunable White technology. DMX Controller. Gimbal mounted, 360° rotatable and 30° tiltable.


The concrete-pour installation blockout is supplied as standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

| | |
|--------------------|--|
| Body | Luminaire body constructed of deep drawn stainless steel. Outer housing composite material. |
| Lens | 5/8" thick clear tempered glass lens. Max. load 5000kg/11,000 lbs. |
| Colors |  Stainless Steel |
| Gasket | Silicone CCG® Controlled Compression Gasket |
| Ingress protection | IP67 |
| Impact resistance | IK10+ |

Electrical description

| | |
|-------------------|--|
| Power supply | Integral [ECG] electronic driver 120V-277V. DMX controlled. Controller to be ordered separately. |
| Termination | Factory sealed termination chamber |
| Surge protection | 1/2 kV (optional SP10) |
| Energy efficiency | D (Light source) |

Additional information

| | |
|-------------------|--|
| Diameter (inches) | 9.84 |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |
| Lifetime | Ta=25°/40° L90B10 > 90000h |

Options

Light distribution **Color temperature** **Nominal Watt**



[B]

2200-6000K

19 W






[M]



[A20]

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI |
|---|----------|-----------------------|------------------|-------------------|-----|
|  [A20] | 185-3396 | LED-12/19W/2200-6000K | 1678.5 lm | 19 W | 80 |
|  [B] | 185-3393 | LED-12/19W/2200-6000K | 1758.3 lm | 19 W | 80 |
|  [M] | 185-3394 | LED-12/19W/2200-6000K | 1837.5 lm | 19 W | 80 |