

Description


IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. 1-10 V analogue dimming (where applicable) available on request. Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP68
Impact resistance	IK10+
Corrosion resistance	-

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Warranty void if installed without proper drainage.

Additional information

Options**Light distribution Colour temperature Nominal Watt**

[M]




3000K

6 W



[EE]



4000K






[EES]



2700K

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [EE]	185-9976	LED-3/6W/2700K	605.8 lm	6 W	80
	185-9927	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9927	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9927	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9930	LED-3/6W/4000K	695.6 lm	6 W	80
	185-9930	LED-3/6W/4000K	695.6 lm	6 W	80
	185-9930	LED-3/6W/4000K	695.6 lm	6 W	80
 [EES]	185-9977	LED-3/6W/2700K	652.3 lm	6 W	80
	185-9928	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9928	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9928	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9931	LED-3/6W/4000K	749 lm	6 W	80
	185-9931	LED-3/6W/4000K	749 lm	6 W	80
	185-9931	LED-3/6W/4000K	749 lm	6 W	80
 [M]	185-9975	LED-3/6W/2700K	648.3 lm	6 W	80
	185-9926	LED-3/6W/3000K	696.3 lm	6 W	80
	185-9926	LED-3/6W/3000K	696.3 lm	6 W	80
	185-9929	LED-3/6W/4000K	744.3 lm	6 W	80
	185-9929	LED-3/6W/4000K	744.3 lm	6 W	80