**Description**


IP68. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

| | |
|--------------------|--|
| Body | Stainless steel construction |
| Lens | Safety glass lens, max. load 5 tonnes |
| Colours |  Stainless Steel |
| Gasket | Silicone rubber gasket |
| Fasteners | PCS hardware |
| Ingress protection | IP68 |
| Impact resistance | IK10+ |

Electrical description

| | |
|------------------|----------------------------------|
| Driver / Ballast | Integral EC electronic converter |
|------------------|----------------------------------|

Additional information

Options**Light distribution Colour temperature Nominal Watt**

[M]




3000K

6 W



[EE]



4000K






[EES]



2700K

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--|----------|----------------|--------------|-------------------|-----|
|  [EE] | 185-9976 | LED-3/6W/2700K | 605.8 lm | 6 W | 80 |
| | 185-9927 | LED-3/6W/3000K | 650.7 lm | 6 W | 80 |
| | 185-9927 | LED-3/6W/3000K | 650.7 lm | 6 W | 80 |
| | 185-9927 | LED-3/6W/3000K | 650.7 lm | 6 W | 80 |
| | 185-9930 | LED-3/6W/4000K | 695.6 lm | 6 W | 80 |
| | 185-9930 | LED-3/6W/4000K | 695.6 lm | 6 W | 80 |
| | 185-9930 | LED-3/6W/4000K | 695.6 lm | 6 W | 80 |
|  [EES] | 185-9977 | LED-3/6W/2700K | 652.3 lm | 6 W | 80 |
| | 185-9928 | LED-3/6W/3000K | 700.7 lm | 6 W | 80 |
| | 185-9928 | LED-3/6W/3000K | 700.7 lm | 6 W | 80 |
| | 185-9928 | LED-3/6W/3000K | 700.7 lm | 6 W | 80 |
| | 185-9931 | LED-3/6W/4000K | 749 lm | 6 W | 80 |
| | 185-9931 | LED-3/6W/4000K | 749 lm | 6 W | 80 |
| | 185-9931 | LED-3/6W/4000K | 749 lm | 6 W | 80 |
|  [M] | 185-9975 | LED-3/6W/2700K | 648.3 lm | 6 W | 80 |
| | 185-9926 | LED-3/6W/3000K | 696.3 lm | 6 W | 80 |
| | 185-9926 | LED-3/6W/3000K | 696.3 lm | 6 W | 80 |
| | 185-9929 | LED-3/6W/4000K | 744.3 lm | 6 W | 80 |
| | 185-9929 | LED-3/6W/4000K | 744.3 lm | 6 W | 80 |