

Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD- optimised optics for superior illumination and glare control. Luminaire requires installation blackout and sealable junction box, which are included in supply.


2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP69





Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.




Additional information

Options

Light distribution

	[M] symmetric, medium beam
	[EE] symmetric, very narrow beam
	[B] symmetric, wide beam
	[EES] symmetric, very narrow beam, sharp cut-off





Colour temperature

	3000K
	4000K
	2700K

Nominal Watt

12 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7271	LED-6/12W/2700K	1269.5 lm	12 W	80
	185-7689	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-7691	LED-6/12W/4000K	1457.5 lm	12 W	80
[B] symmetric, wide beam					
	185-7273	LED-6/12W/2700K	1393.8 lm	12 W	80
	185-7118	LED-6/12W/3000K	1497 lm	12 W	80
	185-7121	LED-6/12W/4000K	1600.3 lm	12 W	80
[EE] symmetric, very narrow beam					
	185-7274	LED-6/12W/2700K	1512.7 lm	12 W	80
	185-7690	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7692	LED-6/12W/4000K	1736.8 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	185-7272	LED-6/12W/2700K	1426.1 lm	12 W	80
	185-7117	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7120	LED-6/12W/4000K	1637.4 lm	12 W	80
[M] symmetric, medium beam					