

Description


IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69

Electrical description

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Options

Light distribution



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[B] symmetric, wide beam




[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature



3000K



4000K







2700K

Nominal Watt

12 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7271	LED-6/12W/2700K	1269.5 lm	12 W	80
	185-7689	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-7691	LED-6/12W/4000K	1457.5 lm	12 W	80
[B] symmetric, wide beam					
	185-7273	LED-6/12W/2700K	1393.8 lm	12 W	80
	185-7118	LED-6/12W/3000K	1497 lm	12 W	80
	185-7121	LED-6/12W/4000K	1600.3 lm	12 W	80
[EE] symmetric, very narrow beam					
	185-7274	LED-6/12W/2700K	1512.7 lm	12 W	80
	185-7690	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7692	LED-6/12W/4000K	1736.8 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	185-7272	LED-6/12W/2700K	1426.1 lm	12 W	80
	185-7117	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7120	LED-6/12W/4000K	1637.4 lm	12 W	80
[M] symmetric, medium beam					