


### Description

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. ASC Anti Slip ceramic Coating on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. LED module can be easily removed for upgrading.

The concrete-pour installation blockout is supplied as standard with luminaire.

## Specifications

### Material description

Body	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens	Safety glass lens, max. load 5 tonnes
Colors	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP69
Corrosion resistance	5CE





### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Termination	Factory sealed termination chamber
Energy efficiency	0-10V available in request. Must be factory fitted.





### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	LED >60,000 h Ta 25°C (L70/B10) Control gear >50,000 h Ta 25°C

**Options**

Light distribution	Color temperature	Nominal Watt
 [M] symmetric, medium beam		0 W
 [VN] symmetric, very narrow beam		
 [W] bi-symmetric, wide beam		
 [VNS] symmetric, very narrow beam, sharp cut-off		

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	185-7117_us		1531.8 lm	0 W	80
	185-7120_us		1637.4 lm	0 W	80
[M] symmetric, medium beam					
	185-7118_us		1497 lm	0 W	80
	185-7121_us		1600.3 lm	0 W	80
[VN] symmetric, very narrow beam					
	185-7690_us		1624.7 lm	0 W	80
	185-7692_us		1736.8 lm	0 W	80
[VNS] symmetric, very narrow beam, sharp cut-off					
	185-7689_us		1363.5 lm	0 W	80
	185-7691_us		1457.5 lm	0 W	80
[W] bi-symmetric, wide beam					