

Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface (6 W luminaires only) available on request. Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information

Options

Light distribution



[M] symmetric, medium beam



[EE] symmetric, very narrow beam




[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature



3000K



4000K






2700K

Nominal Watt

6 W

9 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [EE] symmetric, very narrow beam	185-9793	LED-3/6W/2700K	605.8 lm	6 W	80
	185-7024	LED-3/6W/3000K	650.7 lm	6 W	80
	185-7027	LED-3/6W/4000K	695.6 lm	6 W	80
	185-7788	LED-3/9W/2700K	1009.5 lm	9 W	80
 [EES] symmetric, very narrow beam, sharp cut-off	185-9794	LED-3/6W/2700K	652.3 lm	6 W	80
	185-7710	LED-3/6W/3000K	700.7 lm	6 W	80
	185-7712	LED-3/6W/4000K	749 lm	6 W	80
 [M] symmetric, medium beam	185-9792	LED-3/6W/2700K	593.2 lm	6 W	80
	185-7023	LED-3/6W/3000K	637.2 lm	6 W	80
	185-7026	LED-3/6W/4000K	681.1 lm	6 W	80
	185-7787	LED-3/9W/2700K	920.5 lm	9 W	80
	185-7744	LED-3/9W/3000K	965.4 lm	9 W	80
	185-7748	LED-3/9W/4000K	1010.3 lm	9 W	80