

### Description

RGBW Color Changer.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. LED circuit board. Color Boost technology. Advanced thermal management protects LEDs while optimizing lumens output. LED boards can be easily removed for upgrading. DMX interface. For other control interface options to suit specific project requirements, contact WE-EF.


The concrete-pour installation blockout is supplied as standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Colors	 Stainless Steel
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP69
Impact resistance	IK10+



### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter with DMX Interface
Termination	Factory sealed termination chamber



### Additional information

Listings	Contact WE-EF USA for ETL certification status.
Lifetime	LED >60,000 h Ta 25°C (L70/B10) Control gear >50,000 h Ta 25°C

**Options**

Light distribution	Color temperature	Nominal Watt
 [B] symmetric, wide beam	4000K+RGBW	19 W
 [M] symmetric, medium beam		

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	185-7792	LED-12/19W/4000K+RGBW	1483.8 lm	19 W	80
[B] symmetric, wide beam					
	185-7793	LED-12/19W/4000K+RGBW	1479.5 lm	19 W	80
[M] symmetric, medium beam					