

### Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD- optimised optics for superior illumination and glare control. Luminaire requires installation blackout and sealable junction box, which are included in supply.

2700 K option available on request.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP69

---

### Electrical description

---






Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.

---




### Additional information

## Options

### Light distribution

-  [EE] symmetric, very narrow beam
-  [M] symmetric, medium beam
-  [B] symmetric, wide beam
-  [EES] symmetric, very narrow beam, sharp cut-off
-  [A6] asymmetric, wallgrazer






### Colour temperature

-  3000K
-  4000K
-  2700K

### Nominal Watt

24 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7882	LED-12/24W/2700K	2506.1 lm	24 W	80
	185-7880	LED-12/24W/3000K	2691.7 lm	24 W	80
	185-7881	LED-12/24W/4000K	2877.4 lm	24 W	80
[A6] asymmetric, wallgrazer					
	185-7276	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7693	LED-12/24W/3000K	2631 lm	24 W	80
	185-7695	LED-12/24W/4000K	2812.4 lm	24 W	80
[B] symmetric, wide beam					
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
[EE] symmetric, very narrow beam					
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
[M] symmetric, medium beam					