

Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD- optimised optics for superior illumination and glare control. Luminaire requires installation blockout and sealable junction box, which are included in supply.


2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description









Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP69

Electrical description






Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information

Options**Light distribution Colour temperature Nominal Watt**

	[EE]		3000K	24 W
	[M]		4000K	
	[B]		2700K	
	[EES]			
	[A6]			

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7882	LED-12/24W/2700K	2506.1 lm	24 W	80
	185-7880	LED-12/24W/3000K	2691.7 lm	24 W	80
	185-7881	LED-12/24W/4000K	2877.4 lm	24 W	80
[A6]					
	185-7276	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7693	LED-12/24W/3000K	2631 lm	24 W	80
	185-7695	LED-12/24W/4000K	2812.4 lm	24 W	80
[B]					
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
[EE]					
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
[EES]					
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
[M]					