


**Description**

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.


Luminaire installation blackout and sealable junction box included in supply.



## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69

---

### Electrical description









---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------






---

### Additional information

**Options****Light distribution    Colour temperature    Nominal Watt**

 [EE]	 3000K	24 W
 [M]	 4000K	
 [B]	 2700K	
 [EES]		
 [A6]		

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7882	LED-12/24W/2700K	2506.1 lm	24 W	80
	185-7880	LED-12/24W/3000K	2691.7 lm	24 W	80
	185-7881	LED-12/24W/4000K	2877.4 lm	24 W	80
[A6]					
	185-7276	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7693	LED-12/24W/3000K	2631 lm	24 W	80
	185-7695	LED-12/24W/4000K	2812.4 lm	24 W	80
[B]					
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
[EE]					
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
[EES]					
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
[M]					