


### Description

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. ASC Anti Slip ceramic Coating on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. LED module can be easily removed for upgrading.

The concrete-pour installation blockout is supplied as standard with luminaire.

## Specifications

### Material description

Body	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens	Safety glass lens, max. load 5 tonnes
Colors	 Stainless Steel
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP69
Corrosion resistance	5CE








### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Termination	Factory sealed termination chamber
Energy efficiency	0-10V available in request. Must be factory fitted.





### Additional information

Diameter (inches)	9.84
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	LED >60,000 h Ta 25°C (L70/B10) Control gear >50,000 h Ta 25°C

**Options**

Light distribution	Color temperature	Nominal Watt
 [EE]	 3000K	24 W
 [M]	 4000K	
 [B]	 2700K	
 [EES]		

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	185-7276	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7693	LED-12/24W/3000K	2631 lm	24 W	80
	185-7695	LED-12/24W/4000K	2812.4 lm	24 W	80
[B]					
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7278	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7032	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7036	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7279	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7694	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7696	LED-12/24W/4000K	3242.2 lm	24 W	80
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7277	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7033	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80
	185-7037	LED-12/24W/4000K	3227.8 lm	24 W	80