




### Description

Tunable White.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. LED circuit board. Tunable White technology. Advanced thermal management protects LEDs while optimizing lumens output. LED boards can be easily removed for upgrading. 0-10V Dimming. For other control interface options to suit specific project requirements, contact WE-EF.



The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black).  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

---

Body	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Colors	 Stainless Steel
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP69
Impact resistance	IK10+

---

### Electrical description

---

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Termination	Factory sealed termination chamber

---



### Additional information

---



Diameter (inches)	9.84
Listings	Contact WE-EF USA for ETL certification status.
Lifetime	LED >60,000 h Ta 25°C (L70/B10) Control gear >50,000 h Ta 25°C

---

**Options**

Light distribution	Color temperature	Nominal Watt
 [B]	2200-6000K	19 W
 [M]		

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	185-7789	LED-12/19W/2200-6000K	1758.3 lm	19 W	80
[B]					
	185-7790	LED-12/19W/2200-6000K	1837.5 lm	19 W	80
[M]					