

Description


IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware





Electrical description

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------




Additional information

Options

Light distribution

	[EES] symmetric, very narrow beam, sharp cut-off
	[EE] symmetric, very narrow beam
	[M] symmetric, medium beam
	[B] symmetric, wide beam





Colour temperature

	3000K
	4000K
	2700K

Nominal Watt

12 W
18 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	185-7831	LED-6/12W/2700K	1224.8 lm	12 W	80
	185-9672	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-9676	LED-6/12W/4000K	1457.5 lm	12 W	80
	185-7834	LED-6/18W/2700K	1809.3 lm	18 W	80
	185-7762	LED-6/18W/3000K	1897.5 lm	18 W	80
	185-7766	LED-6/18W/4000K	1985.8 lm	18 W	80
 [EE] symmetric, very narrow beam	185-7829	LED-6/12W/2700K	1393.8 lm	12 W	80
	185-7232	LED-6/12W/3000K	1497 lm	12 W	80
	185-7235	LED-6/12W/4000K	1600.3 lm	12 W	80
	185-7833	LED-6/18W/2700K	1951.4 lm	18 W	80
	185-7761	LED-6/18W/3000K	2046.6 lm	18 W	80
	185-7765	LED-6/18W/4000K	2141.8 lm	18 W	80
 [EES] symmetric, very narrow beam, sharp cut-off	185-7830	LED-6/12W/2700K	1512.7 lm	12 W	80
	185-7227	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7229	LED-6/12W/4000K	1736.8 lm	12 W	80
 [M] symmetric, medium beam	185-7828	LED-6/12W/2700K	1426.1 lm	12 W	80
	185-7233	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7236	LED-6/12W/4000K	1637.4 lm	12 W	80
	185-7832	LED-6/18W/2700K	2062 lm	18 W	80
	185-7760	LED-6/18W/3000K	2162.6 lm	18 W	80
	185-7764	LED-6/18W/4000K	2263.2 lm	18 W	80