

Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes.

Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description








| | |
|-----------|--|
| Body | Stainless steel construction |
| Lens | Safety glass lens, max. load 5 tonnes |
| Colours |  Stainless Steel |
| Gasket | Silicone rubber gasket |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware (unpainted) |

Electrical description





| | |
|-------------------|--|
| Power supply | 230V / 50 Hz |
| Driver / Ballast | Integral EC electronic converter |
| Termination | Junction box supplied |
| Energy efficiency | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage. |

Additional information

Options**Light distribution Colour temperature Nominal Watt**

| | | | | |
|---|-------|---|-------|--------------|
|  | [EES] |  | 3000K | 12 W 18 W |
|  | [EE] |  | 4000K | |
|  | [M] |  | 2700K | |
|  | [B] | | | |

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|-----------------|--------------|-------------------|-----|
|  [B] | 185-7831 | LED-6/12W/2700K | 1224.8 lm | 12 W | 80 |
| | 185-9672 | LED-6/12W/3000K | 1363.5 lm | 12 W | 80 |
| | 185-9676 | LED-6/12W/4000K | 1457.5 lm | 12 W | 80 |
| | 185-7834 | LED-6/18W/2700K | 1809.3 lm | 18 W | 80 |
| | 185-7762 | LED-6/18W/3000K | 1897.5 lm | 18 W | 80 |
| | 185-7766 | LED-6/18W/4000K | 1985.8 lm | 18 W | 80 |
|  [EE] | 185-7829 | LED-6/12W/2700K | 1393.8 lm | 12 W | 80 |
| | 185-7232 | LED-6/12W/3000K | 1497 lm | 12 W | 80 |
| | 185-7235 | LED-6/12W/4000K | 1600.3 lm | 12 W | 80 |
| | 185-7833 | LED-6/18W/2700K | 1951.4 lm | 18 W | 80 |
| | 185-7761 | LED-6/18W/3000K | 2046.6 lm | 18 W | 80 |
| | 185-7765 | LED-6/18W/4000K | 2141.8 lm | 18 W | 80 |
|  [EES] | 185-7830 | LED-6/12W/2700K | 1512.7 lm | 12 W | 80 |
| | 185-7227 | LED-6/12W/3000K | 1624.7 lm | 12 W | 80 |
| | 185-7229 | LED-6/12W/4000K | 1736.8 lm | 12 W | 80 |
|  [M] | 185-7828 | LED-6/12W/2700K | 1426.1 lm | 12 W | 80 |
| | 185-7233 | LED-6/12W/3000K | 1531.8 lm | 12 W | 80 |
| | 185-7236 | LED-6/12W/4000K | 1637.4 lm | 12 W | 80 |
| | 185-7832 | LED-6/18W/2700K | 2062 lm | 18 W | 80 |
| | 185-7760 | LED-6/18W/3000K | 2162.6 lm | 18 W | 80 |
| | 185-7764 | LED-6/18W/4000K | 2263.2 lm | 18 W | 80 |