

Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

Electrical description

Driver / Ballast	Integral EC electronic converter

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
[EES]	3000K	12 W
[EE]	4000K	18 W
[M]	2700K	
[B]		

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[B]	185-7831	LED-6/12W/2700K	1224.8 lm	12 W	80
	185-9672	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-9676	LED-6/12W/4000K	1457.5 lm	12 W	80
	185-7834	LED-6/18W/2700K	1809.3 lm	18 W	80
	185-7762	LED-6/18W/3000K	1897.5 lm	18 W	80
	185-7766	LED-6/18W/4000K	1985.8 lm	18 W	80
[EE]	185-7829	LED-6/12W/2700K	1393.8 lm	12 W	80
	185-7232	LED-6/12W/3000K	1497 lm	12 W	80
	185-7235	LED-6/12W/4000K	1600.3 lm	12 W	80
	185-7833	LED-6/18W/2700K	1951.4 lm	18 W	80
	185-7761	LED-6/18W/3000K	2046.6 lm	18 W	80
	185-7765	LED-6/18W/4000K	2141.8 lm	18 W	80
[EES]	185-7830	LED-6/12W/2700K	1512.7 lm	12 W	80
	185-7227	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7229	LED-6/12W/4000K	1736.8 lm	12 W	80
[M]	185-7828	LED-6/12W/2700K	1426.1 lm	12 W	80
	185-7233	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7236	LED-6/12W/4000K	1637.4 lm	12 W	80
	185-7832	LED-6/18W/2700K	2062 lm	18 W	80
	185-7760	LED-6/18W/3000K	2162.6 lm	18 W	80
	185-7764	LED-6/18W/4000K	2263.2 lm	18 W	80

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia