

### Description

RGBW Colour Changer. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

## Specifications

### Material description

---

Colours



Stainless Steel

Ingress protection IP69

Impact resistance IK10+

---

### Electrical description

---

Driver / Ballast Integral EC electronic converter with DMX Interface

Energy efficiency The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on [www.we-ef.com](http://www.we-ef.com) for further details. Warranty void if installed without proper drainage.

---

### Additional information

## Options

### Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[A6] asymmetric, wallgrazer

### Colour temperature






4000K

4000K+RGBW

### Nominal Watt

30 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[A6] asymmetric, wallgrazer</p>	185-7890	LED-48/30W/4000K+RGBW	2223.3 lm	30 W	80
 <p>[B] symmetric, wide beam</p>	185-7810	LED-48/30W/4000K	2376.9 lm	30 W	80
 <p>[M] symmetric, medium beam</p>	185-7811	LED-48/30W/4000K+RGBW	2463.8 lm	30 W	80