

Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Colours



Stainless Steel




Ingress protection IP69

Impact resistance IK10+

Electrical description

Driver / Ballast Integral EC electronic converter with DMX Interface

Additional information




Options**Light distribution** [B] symmetric, wide beam [M] symmetric, medium beam [A6] asymmetric, wallgrazer**Colour temperature** 4000K

4000K+RGBW

Nominal Watt

30 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[A6] asymmetric, wallgrazer</p>	185-7890	LED-48/30W/4000K+RGBW	2223.3 lm	30 W	80
 <p>[B] symmetric, wide beam</p>	185-7810	LED-48/30W/4000K	2376.9 lm	30 W	80
 <p>[M] symmetric, medium beam</p>	185-7811	LED-48/30W/4000K+RGBW	2463.8 lm	30 W	80