

Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Colours



Stainless Steel

Ingress protection IP69

Impact resistance IK10+

Electrical description

Driver / Ballast Integral EC electronic converter with DMX Interface

Additional information

Options**Light distribution** **Colour temperature** **Nominal Watt**

[B]



4000K

30 W






[M]

4000K+RGBW



[A6]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A6]	185-7890	LED-48/30W/4000K+RGBW	2223.3 lm	30 W	80
 [B]	185-7810	LED-48/30W/4000K	2376.9 lm	30 W	80
 [M]	185-7811	LED-48/30W/4000K+RGBW	2463.8 lm	30 W	80