


### Description

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. ASC Anti Slip ceramic Coating on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. LED module can be easily removed for upgrading.

The concrete-pour installation blockout is supplied as standard with luminaire.

## Specifications

### Material description

Body	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens	Safety glass lens, max. load 5 tonnes
Colors	 Stainless Steel
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP69
Corrosion resistance	5CE

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Termination	Factory sealed termination chamber
Energy efficiency	0-10V available in request. Must be factory fitted.

### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	LED >60,000 h Ta 25°C (L70/B10) Control gear >50,000 h Ta 25°C

**Options**

**Light distribution**



[W] bi-symmetric, wide beam



[VNS] symmetric, very narrow beam, sharp cut-off



[VN] symmetric, very narrow beam



[M] symmetric, medium beam



[A6] asymmetric, wallgrazer

**Color temperature**

**Nominal Watt**

0 W

36 W



2700K








3000K



4000K

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	185-7888	LED-24/36W/2700K	3604.8 lm	36 W	80
	185-7886	LED-24/36W/3000K	3875.1 lm	36 W	80
	185-7887	LED-24/36W/4000K	4145.5 lm	36 W	80
[A6] asymmetric, wallgrazer	<hr/>				
	185-9749_us		4542.4 lm	0 W	80
	185-9753_us		4859.4 lm	0 W	80
[M] symmetric, medium beam	<hr/>				
	185-9748_us		4439.5 lm	0 W	80
	185-9752_us		4749.2 lm	0 W	80
[VN] symmetric, very narrow beam	<hr/>				
	185-7698_us		4818.2 lm	0 W	80
	185-7700_us		5154.3 lm	0 W	80
[VNS] symmetric, very narrow beam, sharp cut-off	<hr/>				
	185-7697_us		4043.5 lm	0 W	80
	185-7699_us		4325.6 lm	0 W	80
[W] bi-symmetric, wide beam	<hr/>				