

Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD- optimised optics for superior illumination and glare control. Luminaire requires installation blackout and sealable junction box, which are included in supply.


2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP69

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information

Options**Light distribution Colour temperature Nominal Watt**

[B]




3000K

36 W



[EES]



4000K



[EE]



2700K








[M]



[A6]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7888	LED-24/36W/2700K	3604.8 lm	36 W	80
	185-7886	LED-24/36W/3000K	3875.1 lm	36 W	80
	185-7887	LED-24/36W/4000K	4145.5 lm	36 W	80
[A6]					
	185-7697	LED-24/36W/3000K	4043.5 lm	36 W	80
	185-7699	LED-24/36W/4000K	4325.6 lm	36 W	80
[B]					
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
[EE]					
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
[EES]					
	185-9749	LED-24/36W/3000K	4542.4 lm	36 W	80
	185-9749	LED-24/36W/3000K	4542.4 lm	36 W	80
	185-9753	LED-24/36W/4000K	4859.4 lm	36 W	80
	185-9753	LED-24/36W/4000K	4859.4 lm	36 W	80
[M]					