

### Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

---

### Additional information

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]



3000K

36 W



[EES]



4000K



[EE]



2700K








[M]



[A6]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7888	LED-24/36W/2700K	3604.8 lm	36 W	80
	185-7886	LED-24/36W/3000K	3875.1 lm	36 W	80
	185-7887	LED-24/36W/4000K	4145.5 lm	36 W	80
[A6]					
	185-7697	LED-24/36W/3000K	4043.5 lm	36 W	80
	185-7699	LED-24/36W/4000K	4325.6 lm	36 W	80
[B]					
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9748	LED-24/36W/3000K	4439.5 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
	185-9752	LED-24/36W/4000K	4749.2 lm	36 W	80
[EE]					
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7698	LED-24/36W/3000K	4818.2 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
	185-7700	LED-24/36W/4000K	5154.3 lm	36 W	80
[EES]					
	185-9749	LED-24/36W/3000K	4542.4 lm	36 W	80
	185-9749	LED-24/36W/3000K	4542.4 lm	36 W	80
	185-9753	LED-24/36W/4000K	4859.4 lm	36 W	80
	185-9753	LED-24/36W/4000K	4859.4 lm	36 W	80
[M]					