

Description

RGBW Colour Changer. IP67. Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

IMPORTANT!

Inground blockouts must be installed with effective drainage, watch here: <https://vimeo.com/672613058>

Specifications

Material description

Colours



Stainless Steel

Ingress protection IP67

Impact resistance IK10+

Electrical description

Energy efficiency The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information

Options**Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam



3000K+RGBW

25 W



[M] symmetric, medium beam

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|-----------------------|--------------|-------------------|-----|
|  [B] symmetric, wide beam | 185-7804 | LED-12/25W/3000K+RGBW | 2059.3 lm | 25 W | 80 |
|  [M] symmetric, medium beam | 185-7805 | LED-12/25W/3000K+RGBW | 2053.3 lm | 25 W | 80 |