

### Description

RGBW Colour Changer. IP67. Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Colours



Stainless Steel

Ingress protection IP67

Impact resistance IK10+

---

### Electrical description

---

Driver / Ballast Integral EC electronic converter with DMX Interface

---

### Additional information

**Options****Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam



3000K+RGBW

25 W



[M] symmetric, medium beam

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	185-7804	LED-12/25W/3000K+RGBW	2059.3 lm	25 W	80
 [M] symmetric, medium beam	185-7805	LED-12/25W/3000K+RGBW	2053.3 lm	25 W	80