

### Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

---

### Additional information

---

Listings	Listed on the AEMO load table at 30 W (12 LED version)
----------	--

---

## Options

### Light distribution



[B] symmetric, wide beam



[EES] symmetric, very narrow beam, sharp cut-off



[EE] symmetric, very narrow beam




[M] symmetric, medium beam

### Colour temperature



3000K



4000K







2700K

### Nominal Watt

24 W

36 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	185-7820	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7713	LED-12/24W/3000K	2631 lm	24 W	80
	185-7715	LED-12/24W/4000K	2812.4 lm	24 W	80
	185-7825	LED-12/36W/2700K	3618.6 lm	36 W	80
	185-7776	LED-12/36W/3000K	3795.1 lm	36 W	80
	185-7780	LED-12/36W/4000K	3971.6 lm	36 W	80
 [EE] symmetric, very narrow beam	185-7822	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-9721	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-9725	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7827	LED-12/36W/2700K	3902.8 lm	36 W	80
	185-7778	LED-12/36W/3000K	4093.2 lm	36 W	80
	185-7782	LED-12/36W/4000K	4283.6 lm	36 W	80
 [EES] symmetric, very narrow beam, sharp cut-off	185-7823	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7714	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7716	LED-12/24W/4000K	3242.2 lm	24 W	80
 [M] symmetric, medium beam	185-7821	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-9722	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-9726	LED-12/24W/4000K	3227.8 lm	24 W	80
	185-7826	LED-12/36W/2700K	4124.1 lm	36 W	80
	185-7777	LED-12/36W/3000K	4325.2 lm	36 W	80
	185-7781	LED-12/36W/4000K	4526.4 lm	36 W	80