

Description


IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

Electrical description

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Listings	Listed on the AEMO load table at 30 W (12 LED version)
----------	--

Options**Light distribution Colour temperature Nominal Watt**

[B]




3000K

24 W

36 W



[EES]



4000K



[EE]







2700K



[M]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	185-7820	LED-12/24W/2700K	2449.5 lm	24 W	80
	185-7713	LED-12/24W/3000K	2631 lm	24 W	80
	185-7715	LED-12/24W/4000K	2812.4 lm	24 W	80
	185-7825	LED-12/36W/2700K	3618.6 lm	36 W	80
	185-7776	LED-12/36W/3000K	3795.1 lm	36 W	80
	185-7780	LED-12/36W/4000K	3971.6 lm	36 W	80
 [EE]	185-7822	LED-12/24W/2700K	2654.1 lm	24 W	80
	185-9721	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-9725	LED-12/24W/4000K	3047.3 lm	24 W	80
	185-7827	LED-12/36W/2700K	3902.8 lm	36 W	80
	185-7778	LED-12/36W/3000K	4093.2 lm	36 W	80
	185-7782	LED-12/36W/4000K	4283.6 lm	36 W	80
 [EES]	185-7823	LED-12/24W/2700K	2823.9 lm	24 W	80
	185-7714	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7716	LED-12/24W/4000K	3242.2 lm	24 W	80
 [M]	185-7821	LED-12/24W/2700K	2811.3 lm	24 W	80
	185-9722	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-9726	LED-12/24W/4000K	3227.8 lm	24 W	80
	185-7826	LED-12/36W/2700K	4124.1 lm	36 W	80
	185-7777	LED-12/36W/3000K	4325.2 lm	36 W	80
	185-7781	LED-12/36W/4000K	4526.4 lm	36 W	80