

Description

RGBW Colour Changer. IP69. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation.

Integral electronic converter with DMX interface in thermally-separated compartment.

Pre-installation blackout is recommended for mounting, available on request.

Specifications

Material description

Colours

Ingress protection IP67

Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV

Energy efficiency G (Light source)

Additional information

Lifetime Ta=25° L90B10 > 90000h

Options

Light distribution



[A6] asymmetric, wallgrazer


Colour temperature

4000K+RGBW

Nominal Watt

48 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A6] asymmetric, wallgrazer	186-0377	LED-96/48W/4000K+RGBW	3405.9 lm	48 W	80