

### Description

Column Grazer.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. 0-10V Dimming. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

---

|                    |   |
|--------------------|---|
| Colors             |   |
| Gasket             | Silicone CCG® Controlled Compression Gasket |
| Ingress protection | IP67  |
| Impact resistance  | IK08  |

---

### Electrical description

---

|                   |   |
|-------------------|---|
| Power supply      | Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order. |
| Driver / Ballast  | Electronic converter with 0-10V interface   |
| Surge protection  | 1/2 kV  |
| Energy efficiency | D (Light source)  |

---





### Additional information

---


|                            |  |
|----------------------------|--|
| Length x Width<br>(inches) | 36.50 x 1.89   |
| Listings                   | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |
| Lifetime                   | Ta=25°/40° L90B10 > 90000h                                 |

---

**Options**

| Light distribution  | Color temperature   | Nominal Watt |
|---|---|--------------|
|  [A6] |  3000K | 30 W         |
|   |  4000K |              |
|   |  2700K |              |

**Configurations**

| Light distribution   | Part ID  | Light source     | Delivered lumens | Rated input power | CRI |
|--|----------|------------------|------------------|-------------------|-----|
|  | 186-0415 | LED-48/30W/2700K | 3287.1 lm        | 30 W              | 80  |
|  | 186-0372 | LED-48/30W/3000K | 3287.1 lm        | 30 W              | 80  |
|  | 186-0373 | LED-48/30W/4000K | 3287.1 lm        | 30 W              | 80  |

[A6]