

Description

Marker Light.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. 0-10V Dimming. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blackout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors

Ingress protection IP67

Impact resistance IK08

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Electronic converter with 0-10V interface

Surge protection 1/2 kV (optional SP10)

Energy efficiency D (Light source)




Additional information

Length x Width
(inches) 36.50 x 1.89

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

Lifetime Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
[]	 3000K	4 W
		3 W
	R	
	G	
	B	
	 2700K	
 4000K		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
□	186-0362	LED-48/3W/R	98.9 lm	3 W	80
	186-0451	LED-48/4W/2700K	197.7 lm	4 W	80
	186-0359	LED-48/4W/3000K	197.7 lm	4 W	80
	186-0463	LED-48/4W/4000K	197.7 lm	4 W	80
	186-0368	LED-48/4W/B	26.4 lm	4 W	80
	186-0365	LED-48/4W/G	197.7 lm	4 W	80