

Description

IP67, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable. Linear PMMA LED lens. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment. Optional 2200 K version available. To be specified at time of ordering.

The optional installation blockout is recommended for mounting. To be ordered separately.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Marine-grade all aluminium construction. Anodized aluminium extrusion.
Colours	
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK08

Electrical description









Power supply	230V / 50 Hz
Driver / Ballast	Integral electronic converter with DALI interface in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information



Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution

-  [LB] symmetric linear, wide beam
-  [LM] symmetric linear, medium beam
-  [LE] symmetric linear, narrow beam
-  [LEE] symmetric linear, very narrow beam
-  [LA10] asymmetric linear, wallwash
-  [LB/IW] symmetric linear, wide beam
-  [LM/IW] symmetric linear, medium beam
-  [LE/IW] symmetric linear, narrow beam








Colour temperature


-  3000K
-  4000K
-  2700K

Nominal Watt

40 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	186-0449	LED-64/40W/2700K	4099.7 lm	40 W	80
	186-0278	LED-64/40W/3000K	4099.7 lm	40 W	80
	186-0279	LED-64/40W/4000K	4099.7 lm	40 W	80
[LA10] asymmetric linear, wallwash					
	186-0445	LED-64/40W/2700K	3831.5 lm	40 W	80
	186-0266	LED-64/40W/3000K	3831.5 lm	40 W	80
	186-0267	LED-64/40W/4000K	3831.5 lm	40 W	80
[LB] symmetric linear, wide beam					
	186-0487	LED-64/40W/2700K	1703 lm	40 W	80
	186-0404	LED-64/40W/3000K	1703 lm	40 W	80
	186-0405	LED-64/40W/4000K	1703 lm	40 W	80
[LB/IW] symmetric linear, wide beam					
	186-0447	LED-64/40W/2700K	4202.5 lm	40 W	80
	186-0272	LED-64/40W/3000K	4202.5 lm	40 W	80
	186-0273	LED-64/40W/4000K	4202.5 lm	40 W	80
[LE] symmetric linear, narrow beam					
	186-0489	LED-64/40W/2700K	2227.4 lm	40 W	80
	186-0408	LED-64/40W/3000K	2227.4 lm	40 W	80
	186-0409	LED-64/40W/4000K	2227.4 lm	40 W	80
[LE/IW] symmetric linear, narrow beam					
	186-0448	LED-64/40W/2700K	4811.9 lm	40 W	80
	186-0275	LED-64/40W/3000K	4811.9 lm	40 W	80
	186-0276	LED-64/40W/4000K	4811.9 lm	40 W	80
[LEE] symmetric linear, very narrow beam					
	186-0446	LED-64/40W/2700K	4280.8 lm	40 W	80
	186-0269	LED-64/40W/3000K	4280.8 lm	40 W	80
	186-0270	LED-64/40W/4000K	4280.8 lm	40 W	80
[LM] symmetric linear, medium beam					
	186-0488	LED-64/40W/2700K	2137.6 lm	40 W	80

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	186-0406	LED-64/40W/3000K	2137.6 lm	40 W	80
	186-0407	LED-64/40W/4000K	2137.6 lm	40 W	80

[LM/IW] symmetric linear, medium beam