

Description

Tunable White. IP69, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable. PMMA LED lens. Factory installed LED circuit board with Tunable White Technology. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface in thermally-separated compartment.

Pre-installation blackout is recommended for mounting, available on request.

Specifications

Material description

Colours

Ingress protection IP67

Impact resistance IK08

Electrical description


Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV

Energy efficiency D (Light source)

Additional information


Lifetime Ta=25° L90B10 > 90000h

Options**Light distribution****Colour temperature****Nominal Watt**

[LB] symmetric linear, wide beam

2200-6000K

40 W



[LM] symmetric linear, medium beam



[LE] symmetric linear, narrow beam








[LEE] symmetric linear, very narrow beam



[LA10] asymmetric linear, wallwash

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[LA10] asymmetric linear, wallwash</p>	186-0431	LED-128/40W/2200-6000K	3644.1 lm	40 W	80
 <p>[LB] symmetric linear, wide beam</p>	186-0338	LED-128/40W/2200-6000K	3405.8 lm	40 W	80
 <p>[LE] symmetric linear, narrow beam</p>	186-0340	LED-128/40W/2200-6000K	3735.6 lm	40 W	80
 <p>[LEE] symmetric linear, very narrow beam</p>	186-0332	LED-128/40W/2200-6000K	4277.2 lm	40 W	80
 <p>[LM] symmetric linear, medium beam</p>	186-0339	LED-128/40W/2200-6000K	3805.1 lm	40 W	80