

Description

Tunable White. IP67, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED board can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment.

The optional installation blockout is recommended for mounting. To be ordered separately.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Colours

Ingress protection IP67

Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV

Energy efficiency D (Light source)

Additional information

Lifetime $T_a=40^\circ$ L90B10 > 90000h






Options**Light distribution Colour temperature Nominal Watt**

2200-6000K

40 W



Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--|----------|------------------------|--------------|-------------------|-----|
|  <p>[LA10]</p> | 186-0431 | LED-128/40W/2200-6000K | 3644.1 lm | 40 W | 80 |
|  <p>[LB]</p> | 186-0338 | LED-128/40W/2200-6000K | 3405.8 lm | 40 W | 80 |
|  <p>[LE]</p> | 186-0340 | LED-128/40W/2200-6000K | 3735.6 lm | 40 W | 80 |
|  <p>[LEE]</p> | 186-0332 | LED-128/40W/2200-6000K | 4277.2 lm | 40 W | 80 |
|  <p>[LM]</p> | 186-0339 | LED-128/40W/2200-6000K | 3805.1 lm | 40 W | 80 |