

### Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blackout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

---

Colors	
Gasket	Silicone CCG® Controlled Compression Gasket
Ingress protection	IP67
Impact resistance	IK08

---

### Electrical description

---

Power supply	Integral [ECG] electronic driver 120V-277V. DMX Dimmable.
Driver / Ballast	Integral DMX electronic converter
Surge protection	1/2 kV
Energy efficiency	D (Light source)

---

### Additional information

---

Length x Width (inches)	48.31 x 1.89
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

---

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**



[LB]

2200-6000K

40 W



[LM]



[LE]








[LEE]



[LA10]

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[LA10]</p>	186-0431	LED-128/40W/2200-6000K	3644.1 lm	40 W	80
 <p>[LB]</p>	186-0338	LED-128/40W/2200-6000K	3405.8 lm	40 W	80
 <p>[LE]</p>	186-0340	LED-128/40W/2200-6000K	3735.6 lm	40 W	80
 <p>[LEE]</p>	186-0332	LED-128/40W/2200-6000K	4277.2 lm	40 W	80
 <p>[LM]</p>	186-0339	LED-128/40W/2200-6000K	3805.1 lm	40 W	80