

Description

RGBW Color Changer, Column Grazer.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blackout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

| | |
|--------------------|--|
| Body | Marine-grade all aluminum construction. Anodized aluminum extrusion. |
| Colors | |
| Gasket | Silicone CCG® Controlled Compression Gasket |
| Ingress protection | IP67 |
| Impact resistance | IK08 |

Electrical description

| | |
|-------------------|---|
| Power supply | Integral [ECG] electronic driver 120V-277V. DMX Dimmable. |
| Driver / Ballast | Integral DMX driver |
| Surge protection | 1/2 kV |
| Energy efficiency | G (Light source) |

Additional information

| | |
|----------------------------|--|
| Length x Width (inches) | 48.31 x 1.89 |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |
| Lifetime | Ta=25°/40° L90B10 > 90000h |

Options


Light distribution **Color temperature** **Nominal Watt**



4000K+RGBW

64 W

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI |
|--|----------|------------------------|------------------|-------------------|-----|
|  | 186-0378 | LED-128/64W/4000K+RGBW | 4541.2 lm | 64 W | 80 |

[A6]