

Description

IP67*, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED board can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment. Optional 2200 K version available. To be specified at time of ordering.

The optional installation blackout is recommended for mounting. To be ordered separately.

The luminaire is not suitable for permanent underwater operation and must be switched off in the event of flooding.

* Additionally tested to IP66, IP67, IP68 0.1 bar 3h, up to

1 m depth according to DIN EN 60598 and IP69K/80°
according to DIN EN 60529.

Specifications

Material description

Colours

Ingress protection IP67

Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV

Energy efficiency D (Light source)

Additional information

Lifetime $T_a=25^\circ$ L90B10 > 90000h

Options

Light distribution



[A6] asymmetric, wallgrazer

Colour temperature



3000K



4000K




2700K

Nominal Watt

40 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	186-0416	LED-64/40W/2700K	4382.8 lm	40 W	80
	186-0374	LED-64/40W/3000K	4382.8 lm	40 W	80
	186-0375	LED-64/40W/4000K	4382.8 lm	40 W	80

[A6] asymmetric, wallgrazer