

### Description

Tunable White. IP69, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable. PMMA LED lens. Factory installed LED circuit board with Tunable White Technology. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface in thermally-separated compartment.

Pre-installation blackout is recommended for mounting, available on request.

## Specifications

### Material description

---

Colours

Ingress protection IP69

Impact resistance IK08

---

### Electrical description

---

Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV

Energy efficiency D (Light source)

---

### Additional information

---

Lifetime  $T_a=25^\circ$  L90B10 > 90000h

---

**Options****Light distribution**

[A6] asymmetric, wallgrazer


**Colour temperature**

2200-6000K

**Nominal Watt**

10 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A6] asymmetric, wallgrazer	186-0381	LED-32/10W/2200-6000K	3544.3 lm	10 W	80