



Description

IP67, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED board can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment.

The optional installation blackout is recommended for mounting. To be ordered separately.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Colours

Ingress protection IP69

Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Surge protection 1/2 kV (optional SP10)

Energy efficiency The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

Additional information

Lifetime Ta=40° L90B10 > 90000h

Options**Light distribution** **Colour temperature** **Nominal Watt**

[]



3000K

6 W

4 W

R

G

B



2700K

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	186-0363	LED-64/4W/R	131.8 lm	4 W	80
	186-0452	LED-64/6W/2700K	263.7 lm	6 W	80
	186-0360	LED-64/6W/3000K	263.7 lm	6 W	80
	186-0369	LED-64/6W/B	35.2 lm	6 W	80
	186-0366	LED-64/6W/G	263.7 lm	6 W	80