

### Description

Marker Light.

P69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. 0-10V Dimming. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blackout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

---

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

---

Colors	
Gasket	Silicone CCG® Controlled Compression Gasket
Ingress protection	IP69
Impact resistance	IK08

---

### Electrical description

---

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Electronic converter with 0-10V interface
Surge protection	1/2 kV (optional SP10)
Energy efficiency	D (Light source)

---



### Additional information

---

Length x Width (inches)	48.31 x 1.89
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

---

**Options**

Light distribution	Color temperature	Nominal Watt
[]	 3000K	6 W
		4 W
	R	
	G	
	B	
	 2700K	

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
□	186-0363	LED-64/4W/R	131.8 lm	4 W	80
	186-0452	LED-64/6W/2700K	263.7 lm	6 W	80
	186-0360	LED-64/6W/3000K	263.7 lm	6 W	80
	186-0369	LED-64/6W/B	35.2 lm	6 W	80
	186-0366	LED-64/6W/G	263.7 lm	6 W	80