

### Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 1.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

---

### Additional information

## Options

### Light distribution



[B] symmetric, wide beam



[EES] symmetric, very narrow beam, sharp cut-off



[M] symmetric, medium beam




[EE] symmetric, very narrow beam

### Colour temperature



3000K







4000K

### Nominal Watt

24 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7673	LED-12/24W/3000K	2631 lm	24 W	80
	185-7675	LED-12/24W/4000K	2812.4 lm	24 W	80
[B] symmetric, wide beam					
	185-9165	LED-12/24W/3000K	2850.7 lm	24 W	80
	185-9168	LED-12/24W/4000K	3047.3 lm	24 W	80
[EE] symmetric, very narrow beam					
	185-7674	LED-12/24W/3000K	3033.1 lm	24 W	80
	185-7676	LED-12/24W/4000K	3242.2 lm	24 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	185-9164	LED-12/24W/3000K	3019.6 lm	24 W	80
	185-9167	LED-12/24W/4000K	3227.8 lm	24 W	80
[M] symmetric, medium beam					