

#### Description

IP68. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP68
Impact resistance	IK10+

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

---

### Additional information

**Options****Light distribution    Colour temperature    Nominal Watt**

[M]




3000K

6 W



[EE]






4000K



[EES]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [EE]	185-9936	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9936	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9936	LED-3/6W/3000K	650.7 lm	6 W	80
	185-9939	LED-3/6W/4000K	695.6 lm	6 W	80
	185-9939	LED-3/6W/4000K	695.6 lm	6 W	80
	185-9939	LED-3/6W/4000K	695.6 lm	6 W	80
 [EES]	185-9937	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9937	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9937	LED-3/6W/3000K	700.7 lm	6 W	80
	185-9940	LED-3/6W/4000K	749 lm	6 W	80
	185-9940	LED-3/6W/4000K	749 lm	6 W	80
	185-9940	LED-3/6W/4000K	749 lm	6 W	80
 [M]	185-9935	LED-3/6W/3000K	696.3 lm	6 W	80
	185-9935	LED-3/6W/3000K	696.3 lm	6 W	80
	185-9938	LED-3/6W/4000K	744.3 lm	6 W	80
	185-9938	LED-3/6W/4000K	744.3 lm	6 W	80