

### Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Colours

RAL9007

Grey aluminium

Ingress protection IP69

Impact resistance IK10+

### Electrical description

---

Driver / Ballast Integral EC electronic converter with DMX Interface

### Additional information

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]

4000K+RGBW

19 W

30 W






[M]

2200-6000K



[A6]

**Configurations**

| Light distribution   | Part ID  | Light source          | Rated lumens | Rated input power | CRI |
|--|----------|-----------------------|--------------|-------------------|-----|
| <br>[A6] | 185-7896 | LED-24/30W/2200-6000K | 2699.8 lm    | 30 W              | 80  |
| <br>[B]  | 185-7798 | LED-12/19W/4000K+RGBW | 1483.8 lm    | 19 W              | 80  |
| <br>[M] | 185-7799 | LED-12/19W/4000K+RGBW | 1479.5 lm    | 19 W              | 80  |