

**Description**

IP66 . IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone CCG® Controlled Compression Gasket.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control.

## Specifications

### Material description

---

Body	Marine-grade, die-cast aluminium alloy								
Lens	Safety glass lens, hinged								
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9016</b></td><td><b>RAL7016</b></td><td><b>RAL9007</b></td></tr><tr><td>Signal black</td><td>Traffic white</td><td>Anthracite grey</td><td>Grey aluminium</td></tr></table>	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>	Signal black	Traffic white	Anthracite grey	Grey aluminium
<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>						
Signal black	Traffic white	Anthracite grey	Grey aluminium						
Gasket	Silicone CCG® Controlled Compression Gasket								
Fasteners	PCS hardware								
Corrosion resistance	5CE								

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---

---

### Additional information

**Options**

**Light distribution**



[A60] asymmetric, forward throw



[R65]




[S65] asymmetric, side throw

**Colour temperature**



3000K






4000K

**Nominal Watt**

36 W

54 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A60] asymmetric, forward throw	108-7749	LED-18/36W/3000K	3899.5 lm	36 W	80
	108-7750	LED-18/36W/4000K	4168.4 lm	36 W	80
	108-7759	LED-18/54W/3000K	5782 lm	54 W	80
	108-7760	LED-18/54W/4000K	6051.1 lm	54 W	80
 [R65]	108-7747	LED-18/36W/3000K	3810.7 lm	36 W	80
	108-7748	LED-18/36W/4000K	4073.5 lm	36 W	80
	108-7757	LED-18/54W/3000K	5650.3 lm	54 W	80
	108-7758	LED-18/54W/4000K	5913.3 lm	54 W	80
 [S65] asymmetric, side throw	108-7743	LED-18/36W/3000K	4182.7 lm	36 W	80
	108-7744	LED-18/36W/4000K	4471.2 lm	36 W	80
	108-7753	LED-18/54W/3000K	6202 lm	54 W	80
	108-7754	LED-18/54W/4000K	6490.7 lm	54 W	80