

**Description**

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Mounting accessories to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

---

## Specifications

### Material description

Colors	 <b>RAL9004</b>	 <b>RAL9007</b>	 <b>RAL9016</b>	 <b>RAL8019</b>
	Signal black	Grey aluminium	Traffic white	Grey brown
Ingress protection	IP66			
Impact resistance	IK08			

---






### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---




---

### Additional information

**Options**

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	 3000K	18 W 26 W
 [M] symmetric, medium beam	 4000K	
 [VN] symmetric, very narrow beam		

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M] symmetric, medium beam</p>	161-5824_us	LED-6/18W/3000K	2167.2 lm	18 W	80
	161-5826_us	LED-6/18W/4000K	2268 lm	18 W	80
	161-5825_us	LED-6/26W/3000K	2772 lm	26 W	80
	161-5827_us	LED-6/26W/4000K	2898 lm	26 W	80
 <p>[VN] symmetric, very narrow beam</p>	161-5828_us	LED-6/18W/3000K	2165.6 lm	18 W	80
	161-5830_us	LED-6/18W/4000K	2266.4 lm	18 W	80
	161-5829_us	LED-6/26W/3000K	2770 lm	26 W	80
	161-5831_us	LED-6/26W/4000K	2895.9 lm	26 W	80
 <p>[W] bi-symmetric, wide beam</p>	161-5820_us	LED-6/18W/3000K	2018.8 lm	18 W	80
	161-5822_us	LED-6/18W/4000K	2112.7 lm	18 W	80
	161-5821_us	LED-6/26W/3000K	2582.2 lm	26 W	80
	161-5823_us	LED-6/26W/4000K	2699.6 lm	26 W	80