

Description

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Mount permits 350° rotation and 180° tilt.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---

Additional information

Listings	UL 1598, CSA C22.2 #250.0 (Intertek)
----------	--------------------------------------

Options

Light distribution



[W] bi-symmetric, wide beam



[M] symmetric, medium beam




[VN] symmetric, very narrow beam

Color temperature



3000K






4000K

Nominal Watt

18 W

26 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M] symmetric, medium beam</p>	161-5852_us	LED-6/18W/3000K	2167.2 lm	18 W	80
	161-5854_us	LED-6/18W/4000K	2268 lm	18 W	80
	161-5853_us	LED-6/26W/3000K	2772 lm	26 W	80
	161-5855_us	LED-6/26W/4000K	2898 lm	26 W	80
 <p>[VN] symmetric, very narrow beam</p>	161-5856_us	LED-6/18W/3000K	2165.6 lm	18 W	80
	161-5858_us	LED-6/18W/4000K	2266.4 lm	18 W	80
	161-5857_us	LED-6/26W/3000K	2770 lm	26 W	80
	161-5859_us	LED-6/26W/4000K	2895.9 lm	26 W	80
 <p>[W] bi-symmetric, wide beam</p>	161-5848_us	LED-6/18W/3000K	2018.8 lm	18 W	80
	161-5850_us	LED-6/18W/4000K	2112.7 lm	18 W	80
	161-5849_us	LED-6/26W/3000K	2582.2 lm	26 W	80
	161-5851_us	LED-6/26W/4000K	2699.6 lm	26 W	80