

**Description**

IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone CCG<sup>®</sup> Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC<sup>®</sup> One LED Concept.

## Specifications

### Material description






Colours	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
Ingress protection	IP66			
Impact resistance	IK08			

### Electrical description




Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---------------------------------------------------------------------

### Additional information

**Options**

Light distribution	Colour temperature	Nominal Watt
 [B]	 3000K	18 W
		26 W
 [M]	 4000K	
 [EE]		

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	161-5848	LED-6/18W/3000K	2018.8 lm	18 W	80
	161-5850	LED-6/18W/4000K	2112.7 lm	18 W	80
	161-5849	LED-6/26W/3000K	2582.2 lm	26 W	80
	161-5851	LED-6/26W/4000K	2699.6 lm	26 W	80
 [EE]	161-5856	LED-6/18W/3000K	2165.6 lm	18 W	80
	161-5858	LED-6/18W/4000K	2266.4 lm	18 W	80
	161-5857	LED-6/26W/3000K	2770 lm	26 W	80
	161-5859	LED-6/26W/4000K	2895.9 lm	26 W	80
 [M]	161-5852	LED-6/18W/3000K	2167.2 lm	18 W	80
	161-5854	LED-6/18W/4000K	2268 lm	18 W	80
	161-5853	LED-6/26W/3000K	2772 lm	26 W	80
	161-5855	LED-6/26W/4000K	2898 lm	26 W	80