

Description

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Mount permits 350° rotation and 180° tilt.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK08			


Electrical description


Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---


Additional information

Options

Light distribution

 [P65] Type II Medium

 [S70] Type II Short

 [A60] Type IV Very Short

 [R65] Type IV Medium

Color temperature



3000K







4000K

Nominal Watt

18 W

26 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	161-5900_us	LED-6/18W/3000K	1468.7 lm	18 W	80
	161-5902_us	LED-6/18W/4000K	1537 lm	18 W	80
	161-5901_us	LED-6/26W/3000K	1878.6 lm	26 W	80
	161-5903_us	LED-6/26W/4000K	1964 lm	26 W	80
 <p>[P65] Type II Medium</p>	161-5892_us	LED-6/18W/3000K	1523.7 lm	18 W	80
	161-5894_us	LED-6/18W/4000K	1594.6 lm	18 W	80
	161-5893_us	LED-6/26W/3000K	1948.9 lm	26 W	80
	161-5895_us	LED-6/26W/4000K	2037.5 lm	26 W	80
 <p>[R65] Type IV Medium</p>	161-5896_us	LED-6/18W/3000K	1457.1 lm	18 W	80
	161-5898_us	LED-6/18W/4000K	1524.9 lm	18 W	80
	161-5897_us	LED-6/26W/3000K	1863.7 lm	26 W	80
	161-5899_us	LED-6/26W/4000K	1948.5 lm	26 W	80
 <p>[S70] Type II Short</p>	161-5888_us	LED-6/18W/3000K	1597.1 lm	18 W	80
	161-5890_us	LED-6/18W/4000K	1671.3 lm	18 W	80
	161-5889_us	LED-6/26W/3000K	2042.8 lm	26 W	80
	161-5891_us	LED-6/26W/4000K	2135.6 lm	26 W	80