

Description

IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone CCG[®] Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept.

Knuckle permits 350° horizontal and 180° vertical aiming of optics.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK08			






Electrical description

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---




Additional information

Listings	Knuckle permits 350° horizontal and 180° vertical aiming of optics
----------	--

Options

Light distribution	Colour temperature	Nominal Watt
 [B]	 3000K	18 W
		26 W
 [M]	 4000K	
 [EE]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	161-5876	LED-6/18W/3000K	2018.8 lm	18 W	80
	161-5878	LED-6/18W/4000K	2112.7 lm	18 W	80
	161-5877	LED-6/26W/3000K	2582.2 lm	26 W	80
	161-5879	LED-6/26W/4000K	2699.6 lm	26 W	80
 [EE]	161-5884	LED-6/18W/3000K	2165.6 lm	18 W	80
	161-5886	LED-6/18W/4000K	2266.4 lm	18 W	80
	161-5885	LED-6/26W/3000K	2770 lm	26 W	80
	161-5887	LED-6/26W/4000K	2895.9 lm	26 W	80
 [M]	161-5880	LED-6/18W/3000K	2167.2 lm	18 W	80
	161-5882	LED-6/18W/4000K	2268 lm	18 W	80
	161-5881	LED-6/26W/3000K	2772 lm	26 W	80
	161-5883	LED-6/26W/4000K	2898 lm	26 W	80